

Namelist "Probe_Location"

These data define the position of each probe on the domain by means of a coordinate system (X_i, X_j, X_k) related to the geometry chosen (cartesian or cylindrical configuration, see the namelist "Geometric_Layout").

Full data set of the namelist

```
&Probe_Location Xi=-0.50 , Xj= 0.0 , Xk= 0.0 /  
&Probe_Location Xi=-0.70 , Xj= 0.2 , Xk= 0.0 /  
&Probe_Location Xi=-0.80 , Xj= 0.03, Xk= 0.4 /
```

- You also need to set the quantities you want to monitor in the namelist "Probe_Quantities_Enabled" and the field Probe_Recording_Rate in the namelist "Simulation_Management"
- The coordinates are related to the geometry chosen (cartesian or cylindrical configuration, see the namelist "Geometric_Layout").

Definition of the data set

X_i

- Type : Real value
- Coordinate of the probe along the I-direction.

X_j

- Type : Real value
- Coordinate of the probe along the J-direction.

X_k

- Type : Real value
- Coordinate of the probe along the K-direction.

From:

<https://sunfluidh.limsi.fr/> - **Documentation du code de simulation numérique SUNFLUIDH**

Permanent link:

https://sunfluidh.limsi.fr/sunfluidh:probe_location_setup_namelist

Last update: **2019/01/14 11:23**

